

## Proposed Code Change State Form 41186R

RETURN TO: INDIANA DEPARTMENT OF HOMELAND SECURITY CODE SERVICES SECTION

302 W. Washington Street Room W246

Indianapolis, IN 46204

INSTRUCTIONS:

Only TYPED copy accepted.

(KEY- Dashed line through material to be deleted , underline material to be added )

FOR OFFICE USE ONLY

Received 10/13/09

Code 48.5.5-09R

Use second sheet for any material requiring more space.

Osc second sheet for any material	requiring more space.
Code Title	Edition
Indiana Residential Code	2009
Section number and title	Page
403.1.3 Seismic Reinforcing	1
Proponent	Title
SW Indiana Builders and Officials	
Address	Phone
2175 N Cullen Ave Evansville, IN 47715 Room 310, Civic	Center Complex, Evansville, IN 812-479-6026 & 812-436-7868
PROPOSED CODE CHANGE (Check One)	
Change to read as follows Add to read as follows Delete and substitute as follows Delete without substitution	
in SDC C1. In Seismic Design Category C1, as a minimum requirement, two #4 bars shall be placed longitudinally in the bottom of the exterior footings. The required bars shall be placed in the bottom half of the footing, at least 6 inches (152.4 mm) apart and not less than 3 inches (76.2 mm) from the bottom and the sides of the footing.	
REASON	
REVIEW RECOMMENDATION	
Approve	
Disapprove	
Approve as amended	
Further Study	